



APPLICATION
INDUSTRIAL
TRACTOR



INDUSTRIAL TRACTOR TYRES

- Extra wide lugs designed to resist buckling, tearing & cracking.
- Excellent tread wear and road ability, the laterally designed lugs result in even wear.



F-3



AT-999



MPT



MONSTER



POWER LUG R-4

SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
11L-15	F-3	10	8.0	TL	280	11.0	813	32.0	355	14.0	2362	93.0	11	14	1060	2332	3.7	53	110	A8/40 kmph	A8/25mph
33x12.5-15	AT-999	8	10.0	TL	318	12.5	851	33.5	381	15.0	2489	98.0	20	25	2130	4486	3.2	46	131	A8/40 kmph	A8/25mph
11L-16	F-3	12	8.0	TL	280	11.0	820	32.3	381	15.0	2438	96.0	10	14	1250	2750	4.5	64	116	A8/40 kmph	A8/25mph
	F-3	14	8.0	TL	280	11.0	820	32.3	381	15.0	2438	96.0	10	14	1375	3025	4.9	70	119	A8/40 kmph	A8/25mph
11L-16	MONSTER	14	8.0	TL	280	11.0	820	32.3	381	15.0	2438	96.0	22	14	1375	3025	4.9	70	119	A8/40 kmph	A8/25mph
12.5/70-16	AT-999	14	10.0	TL	315	12.4	853	33.6	381	15.0	2590	102.0	20	25	1650	3630	2.7	38	125	A8/40 kmph	A8/25mph
10.5/80-18	MPT	10	9.0	TL	267	10.8	910	35.8	406	16.0	2667	105.0	23	29	1950	4290	3.8	54	131	A8/40 kmph	A8/25mph
12.5/65-18	MPT	12	9.0	TL	305	12.0	950	37.4	415	16.3	2781	109.5	23	29	2450	5390	3.6	51	140	A8/40 kmph	A8/25mph
12.5/80-18	MPT	12	9.0	TL	307	12.1	988	38.9	432	17.0	2896	114.0	24	30	2650	5830	3.7	53	142	A8/40 kmph	A8/25mph
	MPT	16	9.0	TL	307	12.1	988	38.9	432	17.0	2896	114.0	24	30	3150	6930	4.9	70	148	A8/40 kmph	A8/25mph
	MONSTER	16	9.0	TL	305	12.0	975	38.4	432	17.0	2896	114.0	33	44	2650	5830	3.6	55	142	A8/40 kmph	A8/25mph
15.5/60-18	AT-999	14	13.0	TL	401	15.8	950	37.4	432	17.0	2870	113.0	22	28	2400	5280	2.6	38	139	A8/40 kmph	A8/25mph
15.5/70-18	AT-999	10	13.0	TL	401	15.8	1031	40.6	483	19.0	3099	122.0	22	28	2650	5830	2.6	37	139	A8/40 kmph	A8/25mph
17.5/65-20	AT-999	14	14.0	TL	450	17.7	1090	42.9	483	19.0	3302	130.0	25	31	3200	7040	2.4	35	149	A8/40 kmph	A8/25mph
16.9-24	AT-999	12	15.0	TL	450	17.7	1303	51.3	584	23.0	3785	149.0	30	38	3250	7150	2.6	38	149	A8/40 kmph	A8/25mph
16.9-24	AT-999	16	15.0	TL	450	17.7	1303	51.3	584	23.0	3785	149.0	30	38	3900	8580	3.3	48	155	A8/40 kmph	A8/25mph
17.5L-24	AT-999	12	15.0	TL	452	17.8	1270	50.0	559	22.0	3683	145.0	28	35	3159	6950	2.6	38	148	A8/40 kmph	A8/25mph
17.5L-24	AT-999	16	15.0	TL	452	17.8	1270	50.0	559	22.0	3683	145.0	28	35	3790	8338	3.3	48	154	A8/40 kmph	A8/25mph
18.4-24	AT-999	12	16.0	TL	472	18.6	1372	54.0	603	24.0	4039	159.0	28	35	3875	8525	2.5	35	155	A8/40 kmph	A8/25mph
19.5L-24	AT-999	12	17.0	TL	495	19.5	1321	52.0	584	23.0	3835	151.0	28	35	3450	7590	2.3	33	151	A8/40 kmph	A8/25mph
16.9-24	POWER LUG R-4	12	15.0	TL	440	17.3	1308	51.5	584	23.0	3861	152.0	28	35	3250	7150	2.6	38	149	A8/40 kmph	A8/25mph
17.5L-24	POWER LUG R-4	12	15.0	TL	445	17.5	1270	50.0	559	22.0	3683	145.0	28	35	3150	6930	2.6	38	148	A8/40 kmph	A8/25mph
18.4-24	POWER LUG R-4	12	16.0	TL	472	18.6	1375	54.1	603	32.7	4039	159.0	28	35	3875	8525	2.4	35	155	A8/40 kmph	A8/25mph
19.5L-24	POWER LUG R-4	12	17.0	TL	495	19.5	1321	52.1	584	23.0	3835	151.0	28	35	3450	7590	2.0	33	151	A8/40 kmph	A8/25mph
	POWER LUG R-4	16	17.0	TL	495	19.5	1325	51.9	584	23.0	3835	151.0	28	35	4135	9097	3.0	44	157	A8/40 kmph	A8/25mph
	MONSTER	16	17.0	TL	490	19.3	1298	51.1	589	23.2	3835	151.0	38	48	4135	9097	3.0	44	157	A8/40 kmph	A8/25mph
21L-24	POWER LUG R-4	12	18.0	TL	533	21.0	1377	54.2	610	24.0	3988	157.0	29	36	3875	8525	2.1	31	155	A8/40 kmph	A8/25mph
18.4-26	AT-999	12	16.0	TL	480	18.9	1422	56.0	635	25.0	4140	163.0	30	38	4010	8822	2.4	36	156	A8/40 kmph	A8/25mph
MONSTER					UNDER DEVELOPMENT																
	POWER LUG R-4	12	16.0	TL	475	18.7	1425	56.1	635	25.0	4191	165.0	28	38	4000	8800	2.4	36	156	A8/40 kmph	A8/25mph
	POWER LUG R-4	16	16.0	TL	475	18.7	1425	56.1	635	25.0	4191	165.0	28	38	4375	9625	2.8	41	159	A8/40 kmph	A8/25mph
16.9-28 MONSTER					UNDER DEVELOPMENT																
	AT-999	12	15.0	TL	450	17.7	1410	55.5	635	25.0	4140	163.0	30	38	3550	7810	2.6	38	152	A8/40 kmph	A8/25mph
	POWER LUG R-4	12	15.0	TL	440	17.3	1410	55.5	635	25.0	4140	163.0	30	38	3550	7810	2.6	38	152	A8/40 kmph	A8/25mph
16.9-30	POWER LUG R-4	12	15.0	TL	440	17.3	1460	57.5	660	26.0	4216	166.0	30	38	3650	8030	2.4	36	153	A8/40 kmph	A8/25mph

Tolerances: O.D. ± 2.5% - S.W. ± 2.5% - RC ± 2.5%