



APPLICATION
CONSTRUCTION
MACHINERY



SKID STEER TYRES

- **MONSTER** - Extra deep tread with sturdy lug design. strong casing with heat and cut resistant tread compound provide longer life. Extra thick side wall with rim guard gives protection against damage.



SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
23X8.50-12	MONSTER	8	7.0	TL	216	8.5	584	23.0	254	10.0	1727	68.0	22.0	27.5	690	1518	3.5	50	90	A5/25kmph	A5/16mph
27X8.50-15	MONSTER	10	7.0	TL	218	8.6	676	26.6	305	12.0	2006	79.0	22.0	27.5	1000	2200	4.3	61	106	A5/25kmph	A5/16mph
10-16.5	MONSTER	12	8.25	TL	259	10.2	798	31.4	366	14.4	2337	92.0	43.0	53.7	2180	4796	4.4	64	135	A5/25kmph	A5/16mph
12-16.5	MONSTER	14	9.75	TL	307	12.1	838	33.0	384	15.1	2515	99.0	44.0	55.0	2765	6083	4.8	70	144	A5/25kmph	A5/16mph
14-17.5	MONSTER	14	10.5	TL	358	14.1	935	36.8	427	16.8	2743	108.0	44.0	55.0	3900	8580	5.5	78	155	A5/25kmph	A5/16mph

- **ROCK MASTER** - Deeper depth tyre tread for longer life. Bigger and sturdier blocks. Excellent chip & tear resistance compound. Extra thick side wall with rim guard gives protection against damages.



SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
10-16.5	ROCK MASTER	12	8.25	TL	267	10.5	790	31.1	356	14.0	2337	92	30	37	2180	4796	5.3	75	135	A5/25 kmph	A5/16mph
12-16.5	ROCK MASTER	14	9.75	TL	325	12.8	856	33.7	381	15.0	2514	99	34	43	2765	6083	4.9	70	144	A5/25 kmph	A5/16mph

- **ROCKPLUS HD** - Deep tread, extra thick sidewall & tough casing ensure longer life. silica & natural rubber base compound provides greater chip & tear resistance.



SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
10-16.5	ROCK PLUS HD	12	8.25	TL	268	10.5	790	31.1	356	14.0	2286	90.0	30	38	2140	4708	5.2	74	134	A5/25 kmph	A5/16mph
12-16.5	ROCK PLUS HD	14	9.75	TL	325	12.8	866	34.1	381	15.0	2438	96.0	30	38	2240	4928	6.2	89	136	A5/25 kmph	A5/16mph
10.00-20	ROCK PLUS HD	18	7.5	TT	284	11.2	1080	42.5	508	20.0	3175	125.0	30	38	6900	15180	10.2	145	175	A5/25 kmph	A5/16mph
12.00-20	ROCK PLUS HD	20	8.5	TT	320	12.6	1151	45.3	530	20.9	3390	133.5	34	42	9250	20350	10.2	145	185	A5/25 kmph	A5/16mph



- **STEERKING HD+** - Premium conventional skid steer tyre with deeper tread depth, premium compound, large tread lugs * heavier sidewall.



STEERKING HD+

SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
			inch		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
10-16.5	STEERKING HD+	8	8.25	TL	268	10.5	795	31.3	356	14.0	2286	90.0	16	20	1370	3014	4.2	60	119	A5/25 kmph	A5/16mph
	STEERKING HD+	10	8.25	TL	268	10.5	795	31.3	356	14.0	2286	90.0	16	20	1560	3432	5.3	75	123	A5/25 kmph	A5/16mph
12-16.5	STEERKING HD+	10	9.75	TL	325	12.8	853	33.6	381	15.0	2438	96.0	20	25	1860	4092	4.5	64	129	A5/25 kmph	A5/16mph
	STEERKING HD+	12	9.75	TL	325	12.8	853	33.6	381	15.0	2438	96.0	20	25	2060	4532	5.2	74	132	A5/25 kmph	A5/16mph

- **STEER PLUS HD** - Premium tyre with extra deep tread & thick sidewalls providing better traction, puncture resistance and longer life. Specially designed rim guard ensures greater protection against flats & wheel damage in the rim flange area.



STEER PLUS HD

SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
			inch		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
23X8.50-12	STEER PLUS HD	6	7.0	TL	216	8.5	584	23.0	254	10.0	1727	68.0	12	15	615	1353	3.4	50	90	A5/25 kmph	A5/16mph
27X8.50-15	STEER PLUS HD	8	7.0	TL	218	8.6	676	26.6	305	12.0	2006	79.0	12	15	950	2090	4.2	61	106	A5/25 kmph	A5/16mph
31X13-16.5	STEER PLUS HD	14	9.75	TL	328	12.9	803	31.6	356	14.0	2337	92.0	19	24	2435	5357	4.7	68	139	A5/25 kmph	A5/16mph
33X15.5-16.5	STEER PLUS HD	14	12.0	TL	394	15.5	838	33.0	381	15.0	2464	97.0	19	24	3150	6930	5.2	74	148	A5/25 kmph	A5/16mph
14-17.5	STEER PLUS HD	14	10.5	TL	348	13.7	940	37.0	406	16.0	2743	108.0	26	33	2900	6380	5.5	79	145	A5/25 kmph	A5/16mph
15-19.5	STEER PLUS HD	14	11.8	TL	401	15.8	1036	40.8	457	18.0	3048	120.0	26	33	3350	7370	4.8	70	150	A5/25 kmph	A5/16mph

- **STEERKING+** - Wide wall tyres with side wall and rim guard protectors, meant for the value conscious performance oriented applications.



STEERKING +

SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
			inch		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
10-16.5	STEERKING +	10	8.25	TL	268	10.5	795	31.3	356	14.0	2286	90.0	15	19	1565	3443	5.2	75	123	A5/25 kmph	A5/16mph
12-16.5	STEERKING +	12	9.75	TL	312	12.3	825	32.5	381	15.0	2438	96.0	16	20	2060	4532	5.2	75	133	A5/25 kmph	A5/16mph



APPLICATION
CONSTRUCTION
MACHINERY



DRIVE WHEEL

R-3 TYRES

- Tread specially designed to give minimum ground disturbance.
- Suitable for use on orchards, soft soil, road construction and similar applications.



SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
18.4-26	SW-333	12	16.0	TL	475	18.7	1430	56.3	635	25.0	4140	163.0	24	30	3000	6600	2.2	33	146	A6/30 kmph	A6/20mph
23.1-26	SW-333	8	20.0	TL	587	23.1	1560	61.4	686	27.0	4547	179.0	26	33	2900	6380	1.0	16	145	A6/30 kmph	A6/20mph
	SW-333	12	20.0	TL	587	23.1	1560	61.4	686	27.0	4547	179.0	26	33	3650	8030	1.7	26	153	A6/30 kmph	A6/20mph
	SW-333	16	20.0	TL	587	23.1	1560	61.4	686	27.0	4547	179.0	26	33	4375	9625	2.1	33	159	A6/30 kmph	A6/20mph



APPLICATION
CONSTRUCTION
MACHINERY

EXCAVATOR TYRES

- Speedways Excavator Tyres are designed to heavy duty service.
- Specially engineered tread pattern provides excellent traction, good self cleaning as well as good on the road drive ability.



SIZE	PATTERN	PLY RATING	RIM WIDTH		TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
			STD.	ALT.												50KPH / 30MPH MAX LOAD						
			inch	inch		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
8.25-20	EV-999	14	6.5	7.0	TT	236	9.3	980	38.6	457	18.0	2972	117.0	18	23	2065	4543	6.8	98	133	B/50 kmph	B/30mph
9.00-20	EV-999	14	7.0	7.5	TT	257	10.1	1039	40.9	483	19.0	3073	121.0	20	25	2500	5500	7.0	102	140	B/50 kmph	B/30mph
10.00-20	EV-999	16	7.5	8.0	TT	277	10.9	1075	42.3	508	20.0	3175	125.0	24	30	3000	6600	7.6	109	146	B/50 kmph	B/30mph



APPLICATION
CONSTRUCTION
MACHINERY

INDUSTRIAL TYRES

- Premium tyres with superior tread compound, larger tread lugs and extra heavy sidewall.



OFFROADER



DUGRIGGER

SIZE	PATTERN	PLY RATING	RIM WIDTH	TT or TL	SECTION WIDTH		OVERALL DIAMETER		NSD		LOAD CAPACITY		INFLATION PRESSURE		LOAD INDEX	SPEED	
					mm	inch	mm	inch	mm	32nds	kg	lbs	bar	psi		kmph	mph
240/55D17.5	OFFROADER	10	6.75	TL	229	9.0	731	28.7	12	15	2100	4620	7.0	99	134	B/50KMPH	B/30mph
355/55D625	DUGRIGGER	14	11.75	TL	355	14.0	935	36.8	20	25	3550	7810	3.7	53	152	B/50KMPH	B/30mph
385/65D19.5	DUGRIGGER				UNDER DEVELOPMENT												
385/65D22.5	DUGRIGGER				UNDER DEVELOPMENT												