



TRACTOR RADIAL TYRES

70, 80 & 85 SERIES

- Radial tyre with balanced characteristics for a wide range of applications both in the field and on the road.
- Larger ground contact patch makes the tyre well suited for handling grassland.
- Long service life thanks to the use of a wear resistant tread compound.
- Deeper Tread providing longer tyre life.
- Prominent Rim Guard, protecting rim flange from damage.



SIZE	PATTERN	RIM WIDTH		TT or TL	SECTION WIDTH		OVERALL DIAMETER		STATIC LOADED RADIUS		ROLLING CIRCUM ± 2.5 %		NSD		LOAD CAPACITY				INFLATION PRESSURE		LOAD INDEX	SPEED	
		REC	ALT		mm	inch	mm	inch	mm	inch	mm	inch	mm	32nds	25 KMPH MAX LOAD		30 KMPH MAX LOAD		bar	psi		kmph	mph
															kg	lbs	kg	lbs					
280/85 R-24 11.2 R-24 125 A8 /B	SR-888	W 10	W 9	TL	282	11.1	1087	42.8	508	20.0	3429	135.0	41	51	1215	2673	1215	2673	1.6	23	115	B/50kmph	B/30mph
340/85 R-24 13.6 R-24 125 A8 /B	SR-888	W 12	W 11	TL	343	13.5	1188	46.8	533	21.0	3531	139.0	44	55	1650	3630	1650	3630	1.6	23	125	B/50kmph	B/30mph
380/85 R-24 14.9 R-24 131 A8 /B	SR-888	W 12	W 11 W 13	TL	381	15.0	1255	49.4	559	22.0	3706	145.9	44	55	1955	4301	1955	4301	1.6	23	131	B/50kmph	B/30mph
320/85R-28 12.4 R-28 124 A8 /B	SR-888	W 11	W 9 W 10	TL	320	12.6	1255	49.4	559	22.0	3734	147.0	42	53	1600	3520	1600	3520	1.6	23	124	B/50kmph	B/30mph
340/85 R-28 13.6 R-28 127 A8 /B	SR-888	W 12	W 11	TL	353	13.9	1288	50.7	584	23.0	3835	151.0	44	55	1755	3861	1755	3861	1.6	23	127	B/50kmph	B/30mph
380/85 R-28 14.9 R-28 133 A8 /B	SR-888	W 12	W 11 W 13	TL	381	15.0	1356	53.4	610	24.0	4013	158.0	45	56	2060	4532	2060	4532	1.6	23	133	B/50kmph	B/30mph
420/70 R-28 133 A8 /B	SR-777	W 13	W 12 W 14	TL	419	16.5	1349	53.1	610	24.0	3988	157.0	44	55	2064	4540	2064	4540	1.6	23	133	B/50kmph	B/30mph
420/85 R-28 16.9 R-28 139 A8 /B	SR-888	W 15	W 13 W 14	TL	419	16.5	1425	56.1	635	25.0	4242	167.0	50	62	2430	5346	2430	5346	1.6	23	139	B/50kmph	B/30mph
380/85 R-30 14.9 R-30 135 A8 /B	SR-888	W 12	W 11 W 13	TL	381	15.0	1407	55.4	630	24.8	4153	163.5	46	57	2180	4796	2180	4796	1.6	23	135	B/50kmph	B/30mph
420/85 R-30 16.9 R-30 140 A8 /B	SR-888	W 15	W 13 W 14	TL	419	16.5	1476	58.1	660	26.0	4394	173.0	49	61	2500	5500	2500	5500	1.6	23	140	B/50kmph	B/30mph
380/85 R-34 14.9 R-34 137 A8 /B	SR-888	W 12	W 11 W 13	TL	381	15.0	1808	71.2	686	27.0	4470	176.0	45	56	2300	5060	2300	5060	1.6	23	137	B/50kmph	B/30mph
420/85 R-34 16.9 R-34 142 A8 /B	SR-888	W 15	W 13 W 14	TL	419	16.5	1577	62.1	711	28.0	4674	184.0	49	61	2650	5830	2650	5830	1.6	23	142	B/50kmph	B/30mph
460/85 R-34 18.4 R-34 147 A8 /B	SR-888	W 16	W 14 W 15	TL	475	18.7	1646	64.8	737	29.0	4851	191.0	52	65	3082	6780	3082	6780	1.6	23	142	B/50kmph	B/30mph
420/85 R-38 16.9 R-38 144 A8 /B	SR-888	W 15	W 13 W 14	TL	419	16.5	1679	66.1	762	30.0	5004	197.0	51	64	2800	6160	2800	6160	1.6	23	144	B/50kmph	B/30mph
460/85 R-38 18.4 R-38 149 A8 /B	SR-888	W 16	W 14 W 15	TL	455	17.9	1748	68.8	787	31.0	5156	203.0	54	67	3250	7150	3250	7150	1.6	23	149	B/50kmph	B/30mph
520/85 R-38 20.8 R-38 155 A8 /B	SR-888	DW 16	DW 18	TL	516	20.3	1849	72.8	813	32.0	5410	213.0	58	72	3875	8525	3875	8525	1.6	23	155	B/50kmph	B/30mph
480/80 R-42 18.4 R-42 151 A8 /B	SR-888	W 16	DW 16	TL	480	18.9	1836	72.3	762	30.0	5461	215.0	54	68	3450	7590	3450	7590	1.6	23	151	B/50kmph	B/30mph
520/85 R-42 20.8 R-42 155 A8 /B	UNDER DEVELOPMENT																						
480/80 R-46 18.4 R-46 158 A8 /B	SR-888	W 16	DW 16	TL	480	18.9	1933	76.1	889	35.0	5791	228.0	54	68	4259	9370	4259	9370	2.4	34	158	B/50kmph	B/30mph
340/85 R-48 13.6 R-48 152 A8 /B	SR-888	W 12	W 11	TL	353	13.9	1798	70.8	838	33.0	5385	212.0	37	46	3557	7825	3557	7825	4.1	58	152	B/30mph	B/30mph